## Low price for Aluminum Window Bending Machine -Automatic Metal Floor Deck Roll Forming Machine - Haixing Industrial

Automatic metal floor deck roll forming machine parameters		
Feeding platform	1	Frame structure: steel plate welded
	2	roller flatting system and pre-hand cutting system
	3	Advantage: not scratch the surface of metal plate
Roll forming M/C	1	Machine weight: 13 tons
	2	Installation dimensions: 1500*1800*1500mm
	3	Machine under frame: steel 400 H-beam
	4	Sidewall: 45# steel plates
	5	Roller stations: 28 rows
	6	Shaft diameter: 85mm
	7	Side wall plate: 24mm
	8	Main shaft material: 45# steel with finish turning
	9	Roller material: 45# forging steel with chromium plate
	10	Chromium plate thickness: 0.05mm
	11	Motor power: 15kW*2, brand Siemens
	12	Reducer type: 2-8# gear speed reducer-Shanghai, China
	13	Chain wheel and cycle chain: 1.2-inch
	14	Production line speed: 10-12m/minutes
PLC control system	1	Functions: adapts quantity cutting system, length of roof sheet can
		be set on the computer
	2	Tolerance: within 1.0mm
		Frequency converter: Delta
		PLC is Siemens
		Encoder: Omron
		Touchscreen: Delta
	7	Voltage standard: 3 phases 380V/50Hz or according to customer's need
	8	Pressing die material: Cr12
Hydraulic pressing		Quenched treatment 58 to 62°C
device		Length tolerance: ±2mm
		Pump station motor: 5.5kW, LICHAO, Shanghai
		Hydraulic oil: 40#
Hydraulic cutting	_	Functions: adapts electric drive and automatic location system to
device	'	decide the dimension and cut the target
	2	Working method: stop to post then post to cut
		Cutting mold material: Cr12
		Quenched treatment 58 to 62°C
	_	Length tolerance: ±2mm
		Pump station motor: 5.5kW, LICHAO, Shanghai

Machine photos



## Packaging Details:

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

## Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link: <a href="https://www.toprollformingmachine.com/?p=11151">https://www.toprollformingmachine.com/?p=11151</a>