Big discounting Pu Panel Production Line -4 Meters Hydraulic Roof Sheet Bending Machine - Haixing Industrial

| | roof sheet bending machine parameters |
|-------------------------|---|
| Cutting &Hydraulic type | Double guide pillar |
| Hydraulic motor power | 3kw |
| Hydraulic Pressure | 10-12MPa |
| /oltage | 380V/3phase/50 HZ(or as your requirement) |
| Cutting drive | Decelerating motor+ Chain drive gear all by |
| | high-frequency |
| Control System | Panasonic PLC |
| Bending degree | 0-90 |
| Operating mode | Button+ Mitsubishi |
| Main Frame | 300mm/350mm H-Beam or 350mm |
| Backboard Thickness | 17mm |
| Feeding Material | GI/PPGI/PPGL |
| Feeding Thickness | 0.2-0.8mm |
| Feeding Width | 1-4m |
| Effective width | 1-4mm |
| Productivity | 0-60times/min |
| Roller material | 45# steel |
| Cutter material | Cr12 mould steel heat-treated hardness of HRC = 60-62 |
| | degrees |
| Brand Square | A3 35mm thick plate arch |
| Cr-Plating Size | 0.05mm |
| Overall Size | 4300*1200*2100mm |
| Total Weight | 1.8T |
| | Hydraulic motor power Hydraulic Pressure Yoltage Yoltage Cutting drive Control System Bending degree Operating mode Main Frame Backboard Thickness Feeding Material Feeding Thickness Feeding Width Effective width Productivity Roller material Further material Brand Square Cr-Plating Size Overall Size |

Machine photos



Packaging Details :

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link : <u>https://www.toprollformingmachine.com/?p=11608</u>