Factory Outlets Changeable C Z Purlin Roll Forming Machine - Galvanized Curving Roof Machine - Haixing Industrial

Galvanized Curving Roof Machine parameters		
1	Main motor power	5.5kw, 3 phase or as your request
2	Hydraulic motor power	4kw
3	Hydraulic Pressure	10-12MPa
4	Voltage	380V /3phase/ 50 HZ (or as your requirement)
5	Control System	PLC Delta Inverter
6	Main Frame	300mm/350mm H-Beam or 350mm
7	Backboard Thickness	16mm
8	Chain Size	1 Inch
9	Feeding Material	color steel coils
10	Feeding Thickness	0.3-0.8mm
11	Feeding Width	100-1200mm
12	Effective width	840-1050mm
13	Productivity	0-15/min
14	Roll Station	13 roll steps(according to different design)
15	Roller Diameter	70mm(depend on different design)
16	Roller material	45# steel
17	Cutter material	Cr12
18	Cr-Plating Size	0.05mm
19	Overall Size	6800*1400*1150mm
20	Total Weight	5.8T

The advantages of galvanized curving roof machine:

- 1. Our machines can uses galvanized steel sheet, colored armor plate or aluminum plate as the material plate.
- 2. Controlling by computer, PLC display, operation is easy, running is steady and reliable, endurable, maintenance-free.
- 3. We can make and designs will kinds of roll forming machine according to customer's request.

Machine photos:



Product link: https://www.toprollformingmachine.com/?p=11881