China Supplier 🛛 Rain Roof Downspout Roll Forming Machine - Glazed roofing tile roll forming machine - Haixing Industrial

The tiles pressed out by the glazed roofing tile roll forming machine are very beautiful, and the technical parameters of the machine are as follows:

Main motor power	4kW, 3-phase or as your requests
Hydraulic motor power	3kW
Hydraulic pressure	10-12MPa
Voltage	380V/3-phase/50Hz (or as your requirements)
Control system	PLC delta inverter
Mainframe	300/350mm H-beam or 350mm
Backboard thickness	16mm
Chain size	1 Inch
Feeding material	color steel coils
Feeding thickness	0.3-0.8mm
Feeding width	1000mm
Effective width	836mm
Productivity	0-15/min
Roll station	13 roll steps (according to different design)
Roller diameter	70mm (depends on different design)
Roller material	45# steel
Cutter material	Cr12
Cr-plating size	0.05mm
Overall size	6800*1400*1150mm
Total weight	4.8 tons
	Hydraulic motor powerHydraulic pressureVoltageControl systemMainframeBackboard thicknessChain sizeFeeding materialFeeding thicknessFeeding thicknessFeeding widthEffective widthProductivityRoll stationRoller diameterRoller materialCutter materialCr-plating sizeOverall size

Glazed roofing tile roll forming machine components include: Manual un-coiler, Guiding platform, Coil strip leveler, Main machine of roll forming, Electric-motor, Cutting device, Hydraulic station, PLC control and Supporter table.

Machine Details :



Packaging Details :

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Product link : <u>https://www.toprollformingmachine.com/?p=12013</u>