Factory Supply Water Gutter Pipe Cold Roll Forming Machine -4 Meters Hydraulic Roof Sheet Bending Machine - Haixing Industrial

| 4 meters hydraulic roof sheet bending machine parameters | | |
|--|-------------------------|---|
| 1 | Cutting &Hydraulic type | Double guide pillar |
| 2 | Hydraulic motor power | 3kw |
| 3 | Hydraulic Pressure | 10-12MPa |
| 4 | Voltage | 380V/3phase/50 HZ(or as your requirement) |
| 5 | Cutting drive | Decelerating motor+ Chain drive gear all by |
| | | high-frequency |
| 6 | Control System | Panasonic PLC |
| 8 | Bending degree | 0-90 |
| 9 | Operating mode | Button+ Mitsubishi |
| 10 | Main Frame | 300mm/350mm H-Beam or 350mm |
| 11 | Backboard Thickness | 17mm |
| 12 | Feeding Material | GI/PPGI/PPGL |
| | | 0.2-0.8mm |
| 15 | Feeding Width | 1-4m |
| 16 | Effective width | 1-4mm |
| 17 | Productivity | 0-60times/min |
| 20 | Roller material | 45# steel |
| 21 | Cutter material | Cr12 mould steel heat-treated hardness of HRC = 60-62 |
| | | degrees |
| | Brand Square | A3 35mm thick plate arch |
| | Cr-Plating Size | 0.05mm |
| 23 | Overall Size | 4300*1200*2100mm |
| 24 | Total Weight | 1.8T |

Machine photos



Packaging Details:

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link: https://www.toprollformingmachine.com/?p=12119