2017 Latest Design Roof Machine Roll Forming -Trapezoidal Roof Panel Roll Forming Machine - Haixing Industrial

Trapezoidal roof sheets made of trapezoidal roof panel roll forming machines have superior strength.

1Main motor power4kW, 3-phase or as your requests2Hydraulic motor power3kW3Hydraulic pressure10-12MPa4Voltage380V/3-phase/50Hz (or as your requirements)5Control systemPLC delta inverter6Mainframe300/350mm H-beam or 350mm7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm13Productivity0-15/min	Roof roll forming machine parameters			
3Hydraulic pressure10-12MPa4Voltage380V/3-phase/50Hz (or as your requirements)5Control systemPLC delta inverter6Mainframe300/350mm H-beam or 350mm7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	1	Main motor power	4kW, 3-phase or as your requests	
4Voltage380V/3-phase/50Hz (or as your requirements)5Control systemPLC delta inverter6Mainframe300/350mm H-beam or 350mm7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	2	Hydraulic motor power	3kW	
5Control systemPLC delta inverter6Mainframe300/350mm H-beam or 350mm7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	3	Hydraulic pressure	10-12MPa	
6Mainframe300/350mm H-beam or 350mm7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	4	Voltage	380V/3-phase/50Hz (or as your requirements)	
7Backboard thickness16mm8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	5	Control system	PLC delta inverter	
8Chain size1 Inch9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	6	Mainframe	300/350mm H-beam or 350mm	
9Feeding materialcolor steel coils10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	7	Backboard thickness	16mm	
10Feeding thickness0.3-0.8mm11Feeding width1000mm12Effective width850mm	8	Chain size	1 Inch	
11Feeding width1000mm12Effective width850mm	9	Feeding material	color steel coils	
12 Effective width 850mm	10	Feeding thickness	0.3-0.8mm	
	11	Feeding width	1000mm	
13 Productivity 0-15/min	12	Effective width	850mm	
	13	Productivity	0-15/min	
14Roll station13 roll steps (according to different design)	14	Roll station	13 roll steps (according to different design)	
15 Roller diameter 70mm (depends on different design)	15	Roller diameter	70mm (depends on different design)	
16Roller material45# steel	16	Roller material	45# steel	
17 Cutter material Cr12	17	Cutter material	Cr12	
18 Cr-plating size 0.05mm	18	Cr-plating size	0.05mm	
19 Overall size 6800*1400*1150mm	19	Overall size	6800*1400*1150mm	
20 Total weight 4.8 tons	20	Total weight	4.8 tons	

Components:

Manual un-coiler: 1 set

Guiding platform: 1 set

Coil strip leveler: 1 set

Main machine of roll forming: 1 set

Electric-motor: 1 set

Cutting device: 1 set

Hydraulic station: 1 set

PLC control: 1 set

Supporter table: 1 set

Machine picture display



Packaging Details :

1. machine is covered by plastic film.

2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link : <u>https://www.toprollformingmachine.com/?p=12621</u>