Factory Supply Metal Roof Tile Machine -C Purlin Channel Roll Forming Machine - Haixing Industrial

C purlin channel roll forming machine process:

The strip is fed from the tail of the equipment and pressed through various press rolls to form a C-shaped steel to be sent out from the head.

| Purlin roll forming machine technical parameters | | |
|--|---------------------------|---|
| 1 | Suitable to process | Steel plate |
| 2 | Rollers | 12 rows |
| 3 | Dimensions | 11*1.3*1.5m |
| 4 | Power | 11.5kw+7.5kw |
| 5 | Thickness of the plate | 1-3mm |
| 6 | Productivity | 8-10m/min |
| 7 | Middle plate thickness | 20mm |
| 8 | Driving ways | 2.6-inch China wheels and link chain |
| 9 | Diameter and material of | 80mm |
| | the forming axis | |
| 10 | Weight | About 8.5T |
| 11 | Voltage | 380V 50HZ3 phase |
| 12 | Roll material | GCr15(bearing steel)hard chrome plated after heat treatment |
| 13 | Shaft material | 40Cr Modulation of heat treatment after polishing hard |
| | | chromium plating |
| 14 | On both sides of the wall | A3 steel |
| | material | |
| 15 | Frame | International H-beam |
| 16 | Blade material | Cr12Mov |
| 17 | Forming wheel | Bearing steel quenching |

The machine comprises the following parts:

Single-end feeding machine(max capacity 5T), Feeding leveling, Forming system, Straightening mechanism(one word original), At single + double holes, After forming shear system, Supporting material platform(6m).

Machine picture display



Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery)

Product link: https://www.toprollformingmachine.com/?p=13112