Super Purchasing for Roll Forming Gutter Machine -Double Layer Metal Tile Making Machine - Haixing Industrial

Our company has a professional foreign trade and design team. Various roll forming machines can be made. You only need to contact us.

Double Layer Metal Tile Making Machine parameters				
1	Main motor power	4kW, 3-phase or as your requests		
2	Hydraulic motor power	3kW		
3	Hydraulic pressure	10-12MPa		
4	Voltage	380V/3-phase/50Hz (or as your requirements)		
5	Control system	PLC delta inverter		
6	Mainframe	300/350mm H-beam or 350mm		
7	Backboard thickness	16mm		
8	Chain size	1 Inch		
9	Feeding material	color steel coils		
10	Feeding thickness	0.3-0.8mm		
11	Feeding width	1000mm		
12	Effective width	840mm, 850mm		
13	Productivity	0-15/min		
14	Roll station	13 roll steps (according to different design)		
15	Roller diameter	70mm (depends on different design)		
16	Roller material	45# steel		
17	Cutter material	Cr12		
18	Cr-plating size	0.05mm		
19	Overall size	6800*1400*1150mm		
20	Total weight	4.8 tons		

Machine picture display

Components of Double Layer Metal Tile Making Machine

No.	Name	Unit	Quantity
1	Manual decoiler	Set	1
2	Main forming machine	Set	1
3	PLC control system	Set	1
4	Hydraulic pump station	Set	1
5	Post cut	Set	1
6	Electric motor	Set	1
7	Output table	Set	1



Product link : <u>https://www.toprollformingmachine.com/?p=13614</u>