Factory Supply Aluminum Decoiler Machine -Roof Panel Curving Machine - Haixing Industrial

Roof panel curving machine consist of decoiler and its base, coil sheet guiding equipment, roll forming system, post cutting equipment, pressing equipment, post-cutting system, hydraulic station, controlling system, supporter table.

| Roof curving roll forming machine parameters | | |
|--|-----------------------------|---|
| 1 | Suitable material | Color galvanized steel coil |
| 2 | Thickness of raw material | 0.3-0.7mm |
| 3 | Yield strength of material | 235Mpa |
| 4 | Working Speed | 8-10m/min |
| 5 | Step distance | Adjustable according to requirement (>=250mm) |
| 5 | Decoiler's loading capacity | Max. Capacity: 5000kgs |
| 6 | Controlling system | PLC with best brand |
| 7 | Power | 3+3kw |
| 8 | Voltage | 380V 50Hz 3phases |
| 9 | Cutting way | Motor drive or Hydraulic drive |
| 10 | Machine's size | about 2m*1.5m*1.4m (Depend on final design) |
| 11 | Total Weight | 2.2Tons |

Machine picture display



Packaging Details:

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link: https://www.toprollformingmachine.com/?p=13838