## Renewable Design for Roof Panel Making Machine Production Line -Automatic CZ Shaped Steel Purlin roll Forming Machine - Haixing Industrial

The advantages of the automatic CZ shaped steel purlin roll forming machine are as follows:


- 1. Produce different pur strip sizes without replacing rollers or gaskets.
- 2. Simple operation and low maintenance cost.
- 3. Infinite size (any size within the machine range) helps save material.
- 4. Optional punching at any position on the web and the flange side of the pur strip.

| Purlin roll forming machine parameters |                           |  |
|--|---------------------------|--|
| 1                                      | Suitable to process       | Steel plate  |
| 2                                      | Rollers                   | 18 rows(Before and after the leveling and contains |
|  |                           | no lead to send passes)                            |
| 3                                      | Dimensions                | 11*1.3*1.5m  |
| 4                                      | Power                     | 11.5kw+7.5kw                                       |
| 5                                      | Thickness of the plate    | 1-3mm  |
| 6                                      | Productivity              | 8-10m/min  |
| 7                                      | Middle plate thickness    | 20mm   |
| 8                                      | Driving ways              | 2.6-inch China wheels and link chain               |
| 9                                      | Diameter and material of  | 80mm   |
|  | the forming axis          |  |
| 10                                     | Weight                    | About 8.5T   |
| 11                                     | Voltage                   | 380V 50HZ3 phase                                   |
| 12                                     | Roll material             | GCr15(bearing steel)hard chrome plated after heat  |
|  |                           | treatment  |
| 13                                     | Shaft material            | 40Cr Modulation of heat treatment after polishing  |
|  |                           | hard chromium plating                              |
| 14                                     | On both sides of the wall | A3 steel   |
|  | material                  |  |
| 15                                     | Frame                     | International H-beam                               |
| 16                                     | Blade material            | Cr12Mov  |
| 17                                     | Forming wheel             | Bearing steel quenching                            |

The machine comprises the following parts:

Single-end feeding machine(max capacity 5T), Feeding leveling, Forming system, Straightening mechanism(one word original), At single + double holes, After forming shear system, Supporting material platform(6m)

Machine picture display



Terms:

- 1. Delivery: within 60 days after receiving the deposit
- 2. Package: export standard package for container
- 3. Payment: TT(30% by TT in advance, 70% by TT after inspect the machine before delivery)

Product link : <u>https://www.toprollformingmachine.com/?p=13852</u>