# Wholesale Price China Z Shape Purlin Roll Forming Machines - Steel Colored Stone Coated Production Line - Haixing Industrial

Our Steel Colored Stone Coated Production Line meets the diverse requirements of our customers.

The Steel Colored Stone Coated Production Line is described in detail as follows:

NO. 1 Auto bottom glue spraying section

| | |
|---|---|
| Appearance size | 4000*1000*2000mm |
| Driving section | 3KW Excitation motor or frequency speed regulation (AS per customers' requirements) |
| Automatic pressure spray tank | 1set; Capability:200kg; Range:0.6~1Mpa |
| Automatic glue machine motor | Servo motor; Power:750w; PLC |
| Automatic spray gun | 4 set (spare parts) |
| Dust collecting fan | 1 set; Power: 200w |
| Damp proof lamp | 1 pcs; Power: 100w |
| Conveying device | Chain reciprocating |
| Air compressor | 1 set; Power: 7.5kw |
| Dust control of axial flow fan | 1 set; Power: 200w |
| Agitator | 1 set; Power: 1.5kw |

NO. 2 Auto stone coated section

| | |
|---|---|
| Appearance size | 3500*1000*1500mm |
| Framework | Steel welding |
| Conveying device | Chain reciprocating |
| Automatic sand hopper | 1 set; Capability: 200kg |
| Bucket lift | 1 set |
| Manual sandblast gun | 4 sets |

NO. 3 The first time drying section

| | |
|---|---|
| Appearance size | 25000*1000*1200mm |
| Framework | Steel welding |
| Frame type thermal insulation wall | 1.2mm cold steel with Rock wool |
| Automatic temperature controller | 4 sets; Range: 0°~160° |
| Infrared heating tube | 30pcs; Power: 30kw |
| Conveying device | Chain reciprocating |
| Air cooling device | 1 set; Power: 200w |

NO. 4 Auto face glue spraying section

| | |
|---|---|
| Appearance size | 3000*1000*2000mm |
| Framework | Steel welding |
| Damp proof lamp | 1 pcs; Power:100w |
| Automatic pressure spray tank | 1 set; Capability: 200kg; Range: 0.6~1Mpa |
| Conveying device | Chain reciprocating |
| Automatic spray gun | 4 sets (spare parts) |
| Manual patch glue gun | 4 sets |
| Dust control of axial flow fan | 1 set; Power: 200w |
| Automatic glue machine motor | Servo motor;  Power: 750w |

NO. 5 The second time drying section

| | |
|---|---|
| Appearance size | 30000*1000*1200mm |
| Framework | Steel welding |
| Frame type thermal insulation wall | 1.2mm cold steel with Rock wool |
| Automatic temperature controller | 4 sets; Range: 0°~160° |
| Infrared heating tube | 30pcs; Power: 30kw |
| Conveying device | Chain reciprocating |
| Air cooling device | 1 set; Power: 200w |

Machine Photos：



Packaging Details：

1. Machine is covered by plastic film.

2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Product link：https://www.toprollformingmachine.com/?p=14148