Factory supplied Floor Decking Sheet Rolling Machine - Double Layer Roof Panel Roll Forming Machine - Haixing Industrial

Double layer roof panel roll forming machines can press two types of tiles of different versions.

Roof roll forming machine parameters		
1	Main motor power	4kW, 3-phase or as your requests
2	Hydraulic motor power	3kW
3	Hydraulic pressure	10-12MPa
4	Voltage	380V/3-phase/50Hz (or as your requirements)
5	Control system	PLC delta inverter
6	Mainframe	300/350mm H-beam or 350mm
7	Backboard thickness	16mm
8	Chain size	1 Inch
9	Feeding material	color steel coils
10	Feeding thickness	0.3-0.8mm
11	Feeding width	1000mm
12	Effective width	840mm, 850mm
13	Productivity	0-15/min
14	Roll station	13 roll steps (according to different design)
15	Roller diameter	70mm (depends on different design)
16	Roller material	45# steel
17	Cutter material	Cr12
18	Cr-plating size	0.05mm
19	Overall size	6800*1400*1150mm
20	Total weight	4.8 tons

Components:

Manual un-coiler: 1 set

Guiding platform: 1 set

Coil strip leveler: 1 set

Main machine of roll forming: 2set

Electric-motor: 1 set


Cutting device: 2 set

Hydraulic station: 1 set

PLC control: 1 set

Supporter table: 1 set

Machine picture display



Packaging Details：

1. Machine is covered by plastic film.

2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

1. Delivery: within 60 days after receiving the deposit.

2. Package: export standard package for container.

3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link：https://www.toprollformingmachine.com/?p=14897