

---

## Aluminum Roofing Sheet Roll Forming Machine Double Layle Metal Tile Making Machine

The automatic control system of the whole unit of the tile press adopts a highly integrated network to make the performance of the automation system superior.

Parameters of double layer roll forming machine

1	Main motor power	4kW, 3-phase or as your requests
2	Hydraulic motor power	3kW
3	Hydraulic pressure	10-12MPa
4	Voltage	380V/3-phase/50Hz (or as your requirements)
5	Control system	PLC delta inverter
6	Mainframe	300/350mm H-beam or 350mm
7	Backboard thickness	16mm
8	Chain size	1 Inch
9	Feeding material	color steel coils
10	Feeding thickness	0.3-0.8mm

Machine photos



---

### Components of double layer corrugated roof sheet making machine

No.	Name	Unit	Quantity
1	Manual decoiler	Set	1
2	Main forming machine	Set	1
3	PLC control system	Set	1
4	Hydraulic pump station	Set	1
5	Post cut	Set	1
6	Electric motor	Set	1
7	Output table	Set	1

#### Terms:

1. Delivery: within 60 days after receiving the deposit.
2. Package: export standard package for container.
3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Our company owned professional design team, we can design different profile according customer's demands.

#### Why choose us ?

##### Professional:

With 10 years' professional manufacturing experience in roll forming machinery;

Professional production line,well -trained workers,strict QC standard.

Haixing Industrial Group Co., Ltd. is the biggest and strongest in north China. Our factory is specialized in manufacturing color steel forming machinery, C&Z purlin machine, glazed tile forming machine, steel structural floor panel roll forming machine, sandwich panel roll forming machine, highway guardrail forming machine and other cold roll forming machines.

Product link : <https://www.toprollformingmachine.com/?p=151735>