Aluminum glazed sheet roll forming machine

Aluminum glazed sheet roll forming machine parameters

| 4 | NA - ! | 41.14. 2 |
|----|-----------------------|--|
| l | Main motor power | 4kW, 3 phase or as your requests |
| 2 | Hydraulic motor power | 3kW |
| 3 | Hydraulic pressure | 10-12MPa |
| 4 | Voltage | 380V/ 3 phase/ 50 Hz (or as your requirements) |
| 5 | Control system | PLC delta inverter |
| 6 | Main frame | 300/350 mm H-beam |
| 7 | Backboard thickness | 16 mm |
| 8 | Chain size | 1 Inch |
| 9 | Feeding material | color steel coils |
| 10 | Feeding thickness | 0.3-0.8 mm |
| 11 | Productivity | 0-15/ min |
| 12 | Roll station | 13 roll steps (according to different design) |
| 13 | Roller diameter | 70 mm (depends on different design) |
| 14 | Roller material | 45# steel |
| 15 | Cutter material | Cr12 |
| 16 | Cr-plating size | 0.05 mm |

Aluminum glazed sheet roll forming machine details



Packaging Details:

- 1. The main machine is covered by the plastic film.
- 2. PLC control box, spare parts, and other small parts are packed by wooden carton box.



Product link: https://www.toprollformingmachine.com/?p=180515