

---

## factory low price Colorful Sand Stone Coated Metal Roof Tile Waterproof Roof Tile Composite Slate Roof Tiles Press

We've got the most highly developed manufacturing machines, experienced and qualified engineers and workers, acknowledged good quality management systems and also a friendly specialist gross sales team pre/after-sales support for factory low price Colorful Sand Stone Coated Metal Roof Tile Waterproof Roof Tile Composite Slate Roof Tiles Press, Welcome your enquiry, very best company will be provided with full heart.

We've got the most highly developed manufacturing machines, experienced and qualified engineers and workers, acknowledged good quality management systems and also a friendly specialist gross sales team pre/after-sales support for [Colorful Sand Stone Coated Metal Roof Tile Waterproof Roof Tile](#), [Composite Slate Roof Tiles](#), [Tile Press](#), In the future, we promise to keep offer the high quality and more cost-effective products, the more efficient after sales service to our all customers all over the world for the common development and the higher benefit.

Our Steel Colored Stone Coated Production Line meets the diverse requirements of our customers.

The Steel Colored Stone Coated Production Line is described in detail as follows:

### NO. 1 Auto bottom glue spraying section

|                                |   |
|--------------------------------|---|
| Appearance size                | 4000*1000*2000mm  |
| Driving section                | 3KW Excitation motor or frequency speed regulation (AS per customers' requirements) |
| Automatic pressure spray tank  | 1set; Capability:200kg; Range:0.6~1Mpa  |
| Automatic glue machine motor   | Servo motor; Power:750w; PLC  |
| Automatic spray gun            | 4 set (spare parts)   |
| Dust collecting fan            | 1 set; Power: 200w  |
| Damp proof lamp                | 1 pcs; Power: 100w  |
| Conveying device               | Chain reciprocating   |
| Air compressor                 | 1 set; Power: 7.5kw   |
| Dust control of axial flow fan | 1 set; Power: 200w  |
| Agitator                       | 1 set; Power: 1.5kw   |

### NO. 2 Auto stone coated section

|                       |                          |
|-----------------------|--------------------------|
| Appearance size       | 3500*1000*1500mm         |
| Framework             | Steel welding            |
| Conveying device      | Chain reciprocating      |
| Automatic sand hopper | 1 set; Capability: 200kg |
| Bucket lift           | 1 set                    |
| Manual sandblast gun  | 4 sets                   |

### NO. 3 The first time drying section

|                                    |                                 |
|------------------------------------|---------------------------------|
| Appearance size                    | 25000*1000*1200mm               |
| Framework                          | Steel welding                   |
| Frame type thermal insulation wall | 1.2mm cold steel with Rock wool |
| Automatic temperature controller   | 4 sets; Range: 0°~160°          |
| Infrared heating tube              | 30pcs; Power: 30kw              |
| Conveying device                   | Chain reciprocating             |
| Air cooling device                 | 1 set; Power: 200w              |

---

NO. 4 Auto face glue spraying section

|                                |   |
|--------------------------------|---|
| Appearance size                | 3000*1000*2000mm                          |
| Framework                      | Steel welding                             |
| Damp proof lamp                | 1 pcs; Power:100w                         |
| Automatic pressure spray tank  | 1 set; Capability: 200kg; Range: 0.6~1Mpa |
| Conveying device               | Chain reciprocating                       |
| Automatic spray gun            | 4 sets (spare parts)                      |
| Manual patch glue gun          | 4 sets                                    |
| Dust control of axial flow fan | 1 set; Power: 200w                        |
| Automatic glue machine motor   | Servo motor; Power: 750w                  |

NO. 5 The second time drying section

|                                    |                                 |
|------------------------------------|---------------------------------|
| Appearance size                    | 30000*1000*1200mm               |
| Framework                          | Steel welding                   |
| Frame type thermal insulation wall | 1.2mm cold steel with Rock wool |
| Automatic temperature controller   | 4 sets; Range: 0°~160°          |
| Infrared heating tube              | 30pcs; Power: 30kw              |
| Conveying device                   | Chain reciprocating             |
| Air cooling device                 | 1 set; Power: 200w              |

Machine Photos :



---

Packaging Details :

1. Machine is covered by plastic film.
2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Product link : <https://www.toprollformingmachine.com/?p=25142>