
Hot Sale for New Design New Fashion Roof Tile Ridge Cap Rolling Machine

Our company puts emphasis about the administration, the introduction of talented staff, along with the construction of employees building, seeking hard to boost the standard and liability consciousness of staff members members. Our business successfully attained IS9001 Certification and European CE Certification of Hot Sale for New Design New Fashion Roof Tile Ridge Cap Rolling Machine, We sincerely look forward to hearing from you. Give us a opportunity to show you our professionalism and enthusiasm. We have been sincerely welcome excellent friends from numerous circles at dwelling and overseas occur to cooperate!

Our company puts emphasis about the administration, the introduction of talented staff, along with the construction of employees building, seeking hard to boost the standard and liability consciousness of staff members members. Our business successfully attained IS9001 Certification and European CE Certification of [New Design Roof Tile Ridge Cap Rolling Machine](#), [New Fashion Roof Tile Ridge Cap Rolling Machine](#), [Roof Tile Ridge Cap Rolling Machine](#), Welcome to visit our company and factory, there are various products displayed in our showroom that will meet your expectation, meanwhile, if you are convenient to visit our website, our sales staff will try their efforts to provide you the best service

roof ridge making machine parameters		
1	Decoiler	Manual decoiler or hydraulic decoiler
2	Raw material thickness	0.2-0.8mm
3	Material	As your requirements
4	Machine dimensions	7000*800*1500mm
5	Feeding width	According to your profile
6	Forming station	13 to 15 steps
7	Shaft diameter	75mm
8	Shaft material	High-grade 45# steel, heated and quenched
9	Roller material	High-grade 45# steel, coated with 0.05mm chrome
10	Forming speed	10-15m/minute (adjustable)
11	Transmission type	Chain transmission
12	Machine frame stand	Welded structural steel, thickness is 18mm
13	Main motor	5.5kW from Shanghai, China
14	Cutting type	Stop hydraulic cutting
15	Cutting power	3kW
16	Cutter material	Cr12 with quenched treatment HRC 58-62
17	Cutting length error	±2mm
18	Voltage	380V/50Hz and 3 or according to your requirements
19	Control system	PLC control system
20	Size of PLC	700*1000*300mm
21	PLC	Delta/Siemens

Machine details:



Roof ridge making machine package and shipment details:

Standard export packing: 1 x 40GP container, main machine naked and fastened with iron wire in the container, rollers were painted with oil and packed with plastic film, electric devices be packed with wooden box.

Product link : <https://www.toprollformingmachine.com/?p=26030>