
Roof Sheet Crimping Curved Machine

FAQ

Q: How can we be assured that you will deliver us quality machine with spare parts?

- A: 1. Customers to send the technical people to our factory for checking the quality.
2. We can send the technicians to the buyer`s factory for the installation of the machine.
3. Good aftersales-service, its free of charge during the warranty period.

Q: What can you do if the machine is broken?

A: Our machine's warranty period is 12months, if the broken parts can't repair, we can send the new parts to replace the broken parts freely, but you need to pay the express cost yourself. if after the warranty period, we can look at negotiation to solve the problems, and we supply the technical support for the whole life of the equipment.

Roof Sheet Crimping Curved Machine parameters

Main motor	3kw, Siemens Bede Motor
Hydraulic power station	4kw, gear pump: Shanghai Lichao
Cutter material	Cr12, heat treatment HR50-60
Cutting method	Hydraulic four-column cutting
Length tolerance	±2mm
Number of rows	3 rows
Equipment size	6500*1350*1400mm
Pressing mold material	Cr12
Raw material thickness	0.28~0.8mm

Roof Sheet Crimping Curved Machine Applications

The curved panel is used for the door and wall.

Usually, when raining, the raindrops to the front of your door, and there is some water.

It is not convenient to come in or out. Now with the curved panel, the rain is guided away from your door. It will be cleaner.

It works the same for the wall. With the curved panel, the rain will not leak into your room, also keeps away from the wall panel. Thus the wall panel will endure for longer years.

Packaging and transportation



Product link : <https://www.toprollformingmachine.com/?p=357918>