Supply ODM Double Layer Roofing Making Roll Forming Machine s

Our mission will be to become an innovative supplier of high-tech digital and communication devices by furnishing benefit added structure, world-class manufacturing, and service capabilities for Supply ODM Double Layer Roofing Making Roll Forming Machine s, "Making the Merchandise of Significant Quality" could be the eternal goal of our firm. We make unremitting endeavours to know the aim of "We Will Always Keep in Pace using the Time".

Our mission will be to become an innovative supplier of high-tech digital and communication devices by furnishing benefit added structure, world-class manufacturing, and service capabilities for <u>Double Layer Roll Forming Machine</u>, <u>Double Layer Roofing Sheet Machine</u>, <u>Double Sheets Roll Forming Machine</u>, During the development, our company has built a well-known brand. It is well highly acclaimed by our customers. OEM and ODM are accepted. We are looking forward to customers from all over the world to join us to a wild cooperation.

1 Material width 2 sizes. Waiting for buyer exactly profile 2 How to adjust size Option: by PLC (It can be adjust by PLC and also in hand wheel) One side fixed and the other is adjustable by manual or PLC 3 Base frame base frame base frame 30 mm thick steel plate process the surface on CNC planer to keep it leveling and drill bolts and key slot by CNC 4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA Gr75, coated with chrome HRC58-62 degree 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 4 Cutting Hydraulic post-cutting for cut end product 20 material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 1 ron Cast 1 In main machine and control panel all have emergency switch for forbid any urgently accident. 26 Protect cover Complete mobile safety cover from roll forming to the		Steel profile door frame roll forming machine parameters		
wheel) One side fixed and the other is adjustable by manual or PLC Base frame Base frame base frame 30 mm thick steel plate process the surface on CNC planer to keep it leveling and drill bolts and key slot by CNC 4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material GCr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 13 Maim Motor Power 14 Hydraulic Station Power 15 Hydraulic Pressure 16 Capacity of tonnage for punching 17 Hydraulic pump brand 18 Cutting 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain Yellow and blue 24 Machine Type Iron Cast Iron Marial and In main machine and control panel all have emergency switch for forbid any urgently accident.	1	Material width	3 sizes. Waiting for buyer exactly profile	
One side fixed and the other is adjustable by manual or PLC Base frame base frame 30 mm thick steel plate process the surface on CNC planer to keep it leveling and drill bolts and key slot by CNC Rolling Speed 12-15m/min(not include cutting time) Rolling Thickness 1.2-2.0mm Material GI or metal Control System PLC (Panasonic) as list in the note decoiler 3 Ton manual decoiler Leveling Up in 3 roller, down in 4 roller Roller Stations About 20 stations Roller Material GCr15, coated with chrome HRC58-62 degree degree shaft with chrome HRC58-62 degree steel degree degree for punching for punching for punching degree degre	2	How to adjust size	Option : by PLC (It can be adjust by PLC and also in hand	
Base frame base frame 30 mm thick steel plate process the surface on CNC planer to keep it leveling and drill bolts and key slot by CNC 4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material GCr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 070mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60Hz,3 phase 22 Way Of Drive 1.2 inch single chain 24 Machine Type Iron Cast In main machine and control panel all have emergency switch for forbid any urgently accident.			wheel)	
Base frame base frame 30 mm thick steel plate process the surface on CNC planer to keep it leveling and drill bolts and key slot by CNC 4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material GCr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 170mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast In main machine and control panel all have emergency switch for forbid any urgently accident.			One side fixed and the other is adjustable by manual or	
on CNC planer to keep it leveling and drill bolts and key slot by CNC 4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA			PLC	
Slot by CNC	3	Base frame	· ·	
4 Rolling Speed 12-15m/min(not include cutting time) 5 Rolling Thickness 1.2-2.0mm 6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.			on CNC planer to keep it leveling and drill bolts and key	
5Rolling Thickness1.2-2.0mm6MaterialGI or metal7Control SystemPLC (Panasonic) as list in the note8decoiler3 Ton manual decoiler9LevelingUp in 3 roller, down in 4 roller10Roller StationsAbout 20 stations11Roller MaterialGcr15, coated with chrome HRC58-62 degree12Shaft Material and DIA70mm, material is 45# forge steel13Maim Motor Power11kw brake motor14Hydraulic Station Power5.5kw15Hydraulic Pressure20Mpa16Capacity of tonnage for punching22Tons17Hydraulic pump brandLichao18CuttingHydraulic post-cutting for cut end product19Extra cutterOne more cutter for each profile20Material Of CuttingCr12Mov quenching 58-62°C21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.			1	
6 Material GI or metal 7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 24 Machine Type Iron Cast In main machine and control panel all have emergency switch for forbid any urgently accident.				
7 Control System PLC (Panasonic) as list in the note 8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 24 Machine Type Iron Cast In main machine and control panel all have emergency switch for forbid any urgently accident.			1.2-2.0mm	
8 decoiler 3 Ton manual decoiler 9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.		Material	GI or metal	
9 Leveling Up in 3 roller, down in 4 roller 10 Roller Stations About 20 stations 11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA Tomm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.		-	PLC (Panasonic) as list in the note	
10 Roller Stations 11 Roller Material 12 Shaft Material and DIA 13 Maim Motor Power 14 Hydraulic Station Power 15 Hydraulic Pressure 16 Capacity of tonnage for punching 17 Hydraulic pump brand 18 Cutting 19 Extra cutter 20 Material Of Cutting 20 Material Of Cutting 21 Electric Source 22 Way Of Drive 23 Color Of The Machine 24 Machine Type 10 Shaft Material Of Cutting In Main machine and control panel all have emergency switch or material is 45# forge steel 17 70mm, material is 45# forge steel 18 10 70mm, material is 45# forge steel 19 10 1km brake motor 11kw brake motor 120 Map and blue 121 Capacity of tonnage for punching 5 45 1 1 2 inch single chain 18 Cutting 19 Extra cutter 19 Cr12Mov quenching 58-62°C 20 1 Electric Source 21 Slectric Source 22 Way Of Drive 23 Color Of The Machine 24 Machine Type 25 Emergency switch 26 In main machine and control panel all have emergency switch for forbid any urgently accident.		decoiler	3 Ton manual decoiler	
11 Roller Material Gcr15, coated with chrome HRC58-62 degree 12 Shaft Material and DIA □ 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.	9		Up in 3 roller, down in 4 roller	
12 Shaft Material and DIA ☐ 70mm, material is 45# forge steel 13 Maim Motor Power 11kw brake motor 14 Hydraulic Station Power 5.5kw 15 Hydraulic Pressure 20Mpa 16 Capacity of tonnage for punching 17 Hydraulic pump brand Lichao 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.			About 20 stations	
13Maim Motor Power11kw brake motor14Hydraulic Station Power5.5kw15Hydraulic Pressure20Mpa16Capacity of tonnage for punching22Tons17Hydraulic pump brandLichao18CuttingHydraulic post-cutting for cut end product19Extra cutterOne more cutter for each profile20Material Of CuttingCr12Mov quenching 58-62°C21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.	11	Roller Material	Gcr15, coated with chrome HRC58-62 degree	
14Hydraulic Station Power5.5kw15Hydraulic Pressure20Mpa16Capacity of tonnage for punching22Tons17Hydraulic pump brandLichao18CuttingHydraulic post-cutting for cut end product19Extra cutterOne more cutter for each profile20Material Of CuttingCr12Mov quenching 58-62°C21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.		Shaft Material and DIA		
15 Hydraulic Pressure 16 Capacity of tonnage for punching 17 Hydraulic pump brand 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.	13	Maim Motor Power	11kw brake motor	
16 Capacity of tonnage for punching 17 Hydraulic pump brand 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.	14	Hydraulic Station Power	5.5kw	
punching 17 Hydraulic pump brand 18 Cutting Hydraulic post-cutting for cut end product 19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.			20Мра	
17Hydraulic pump brandLichao18CuttingHydraulic post-cutting for cut end product19Extra cutterOne more cutter for each profile20Material Of CuttingCr12Mov quenching 58-62°C21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.	16	Capacity of tonnage for	22Tons	
18CuttingHydraulic post-cutting for cut end product19Extra cutterOne more cutter for each profile20Material Of CuttingCr12Mov quenching 58-62°C21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.				
19 Extra cutter One more cutter for each profile 20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.		Hydraulic pump brand	Lichao	
20 Material Of Cutting Cr12Mov quenching 58-62°C 21 Electric Source 380V, 60HZ,3 phase 22 Way Of Drive 1.2 inch single chain 23 Color Of The Machine Yellow and blue 24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.	18	Cutting	Hydraulic post-cutting for cut end product	
21Electric Source380V, 60HZ,3 phase22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.	19	Extra cutter	One more cutter for each profile	
22Way Of Drive1.2 inch single chain23Color Of The MachineYellow and blue24Machine TypeIron Cast25Emergency switchIn main machine and control panel all have emergency switch for forbid any urgently accident.	20	Material Of Cutting	Cr12Mov quenching 58-62°C	
23 Color Of The Machine Yellow and blue 24		Electric Source	380V, 60HZ,3 phase	
24 Machine Type Iron Cast 25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.				
25 Emergency switch In main machine and control panel all have emergency switch for forbid any urgently accident.	23	Color Of The Machine	Yellow and blue	
switch for forbid any urgently accident.		Machine Type		
	25	Emergency switch		
26 Protect cover Complete mobile safety cover from roll forming to the				
	26	Protect cover	Complete mobile safety cover from roll forming to the	

		cutter.
27	Size of the machine	L*W*H 12m*1.2m*1.2m
28	Container Need	1 x40 feet (base on final)

The steel door frame roll forming machine is a complete product line. After roll forming by our production line, we could make very smooth and beautiful steel door frame without any scratch on surface.

Machine picture display



Packaging Details:

- 1. Machine is covered by plastic film.
- 2. PLC control box, spare parts and other small parts are packed by wooden carton box.

Terms:

- 1. Delivery: within 60 days after receiving the deposit.
- 2. Package: export standard package for container.
- 3. Payment: TT (30% by TT in advance, 70% by TT after inspect the machine before delivery).

Product link: https://www.toprollformingmachine.com/?p=49880